



MULTI CASSETTE IX43 R32

• On/Off contact and alarm.



Golden Fin protection



DC inverter compressor and fans



Condensate pump



Remote control



Filters easy to clean



Fresh air

MODEL

HTW-MC6-035IX43R32

HTW-MC6-052IX43R32

Power Supply **V,P,HZ** 220-240V (1 Phase ~ 50Hz)

PERFORMANCE

			HTW-MC6-035IX43R32	HTW-MC6-052IX43R32
Cooling	Capacity	kW	3,52	5,2
		Btu/h	12.011	17.743
Heating	Capacity	kW	4,1	5,5
		Btu/h	13.990	18.767

FEATURES

			HTW-MC6-035IX43R32	HTW-MC6-052IX43R32
Indoor unit	Sound power	dB(A)	57	55/52/49
	Sound pressure	dB(A)	35/39/43	42/39/36
	Air flow	m³/h	450/530/650	1.250
	Operating temperature	°C	17~30	16~30

DIMENSIONS AND WEIGHT

			HTW-MC6-035IX43R32	HTW-MC6-052IX43R32
Indoor unit	Net dimensions (WxHxD)	mm	570x260x570 647x50x647 (panel)	570x260x570 647x50x647 (panel)
	Cassette/panel net weight	Kg	16,2 / 2,5	16,2 / 2,5

CONNECTIONS

			HTW-MC6-035IX43R32	HTW-MC6-052IX43R32
Refrigerant pipe	Liquid-Gas	inch	1/4" - 3/8"	1/4"-1/2"
Electrical connections	Supply	mm	from outdoor	from outdoor
	Connection	mm	3 x 2,5 + T	3 x 2,5 + T